Main Features: -

- Welding Nipple W-M
- 1/4" to 4"
- Thread according to ISO 7-1
- Working Temperature -20 to + 220C *
- Max. Working pressure 20 Bar

*Temperature and pressure determined by valve body, seat etc.

Suitable Applications & Approvals:











SERIES: 80409



Ref	SIZE (R)	В	Е	L			
80409-02	1/4"	13.7	2.24	30		_ в _	
80409-03	3/8"	17.1	2.31	30			
80409-04	1/2"	21.3	2.77	35	1		
80409-05	3/4"	26.7	2.87	40			
80409-06	1"	33.4	3.38	40		i E-	
80409-07	1 1/4"	42.2	3.56	50			
80409-08	1 1/2"	48.3	3.68	50			
80409-09	2"	60.3	3.91	50			
80409-10	2 1/2"	76.1	5.16	60			
80409-11	3"	88.9	5.49	70			
80409-12	4"	114.3	6.02	80		R R	

ALLVALVES

Offering a full range of actuated valve packages, manual valve range, pipe fittings and pumps, we have a product for all your requirements. As an ISO 9001-2015 Quality Approved and certified company, All Valves offer a quality service from pre-sale to post sale. Shipping millions of pounds in value of manual valve and actuated valve packages all over the world since its formation, All Valves are a trusted valve and actuator supplier to many companies all over the world. Working with the leading brands in most industries.







