## Main Features: -

- Check Valve Full Bore
- Thread female ends gas (BSP)
- Maximum working pressure 25/18 bar
- Working temperature from -20° C to 90° C
- Minimum opening pressure 0,03 bar

\*Temperature and pressure determined by medium

Suitable Applications & Approvals:











**SERIES: 80626** 



## **MATERIAL ITEM SECTION** ADDITIONAL INFO / OPTIONS Body **Brass** Peened+Chromed 1 Brass+NBR 2 Stem Assembly 3 Spring **AISI 316** 4 Stopper Spring Brass Chromed 5 Filter **AISI 304**

REF	SIZE	PN	DN	Α	D	Kg
80626-04	1/2"	25	15	78	28	0.09
80626-05	3/4"	25	20	91	35	0.15
80626-06	1"	25	25	97	42	0.235
80626-07	11/4"	18	32	113	52	0.340
80626-08	11/2"	18	40	128	63	0.510
80626-09	2"	18	50	150	78	0.760

## **ALL VALVES**

AllValves Online™ have used decades of experience in the valve industry to select a range of products that match the Allvalves Online ethos - value for money. All Valves Products are from reputable sources and have been sold in significant quantities for many years, are installed in a wide variety of applications, and are known to be durable in service.













